


# HC-HV 6-TFL-60/M1PG21S

Order No.: 1773705

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1773705>

Sleeve housing, for single locking latch, height 60 mm, with screw connection, 1x Pg21, lateral cable entry

## Commercial data

GTIN (EAN)	 4 017918 037796
Note	Made-to-order
sales group	D003
Pack	10 pcs.
Customs tariff	85389099
Catalog page information	Page 246 (PC-2005)

## Product notes

WEEE/RoHS-compliant since:  
03/01/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### General data

Note	For contact inserts HV-HV6
Design	HV6
Height	60 mm
Width	43 mm

Length	94 mm
Housing type	Sleeve housings
Locking type	for single locking latch
Cable exit	Lateral
Type of the screw connection	1x Pg21
Pg screw connection	With
Wrench size, union nut	28 mm
External cable diameter	10 mm ... 19 mm
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray
Cable gland material	Nickel-plated brass
Cable seal material	NBR

#### Certificates / Approvals




Certification

GOST

#### Diagrams/Drawings

Dimensioned drawing



**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;